

© Cyber

















© Cyber

This new and luxurious RPET woven upholstery textile is in our www.wovenbottles.com collection.

Woven on an air jet loom with micro-chenille yarns, these yarns provide a voluminous, chunky and comfortable handfeel. Cyber is piece dyed and is suitable for all types of upholstery, such as loose covers, tight fitted or buttoned.

The face-side exists of 96% RPET and 4% virgin nylon and the backing is made from 100% RPET. It is soft and sustainable and besides that also strong and durable.

All certifications are available and available in a wide range of contemporary, commercial and trendy colours from stock.

For loose covers it is also nice to mention that Cyber is machine-washable at 30 degrees Celsius*.

- We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.

Fabraa Upholstery fabrics with a conscience. We make sustainable choices easy by offering a wide range of high-qualty, affordable upholstery fabrics with consideration for the conditions throughout the supply chain.

Composition

/ faceside 96%RPET 4%NY / backside 100%RPET / flatweave

Suitable for

sofa's, beds, chairs with fitted and loose fitting upholstery



Please note: colours may vary according to your screen settings.



thyme 206

Cyber - Article passport

A fabric from micro chenille yarns with extra voluminous and comfortable handfeel.

Available from stock in a wide range of contemporary and commercial colours.

Product	characteristics

Productgroup	flatweave	
Applications	sofa's, beds, chairs with fitted and loose fitting upholstery	
Composition faceside	96%RPET 4%NY	
Composition backside	100%RPET	
Bonding	non-woven	
Statistic code	54075200	
Dyeing method	piece dyed	
Available colours	22	
Packaging	transparent plastic	

Durability specifications

Test		Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09		
					Dry	Wet	DGM	DGM+			
Abrasion resistance - yarn breakage		DIN EN ISO 12947-1:2007-04, DIN EN ISO 12947-2:2017-03	CTL	cycles	90.000		min. 8.000	min. 16.000	В		
Pilling		DIN EN ISO 12945-2:2000-11. 2000 cycles	CTL	grade	4		min. 3-4	min. 4	В		
Colour fastness to light		DIN EN ISO 105-BO2:2014-11. Process 3, exposure level 5									
		light colours	CTL	grade	5		min. 4	min.5	В		
		middle colours	CTL	grade	5		min. 4	min.5	В		
		dark colours	CTL	grade	5		min. 4	min.5	В		
Colour fastness to rubbing		DIN EN ISO 105-X12:2016-11									
	light colours	CTL	grade	4-5	4-5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A			
		middle colours	CTL	grade	4-5	4-5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A		
		dark colours	CTL	grade	4	3-4	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A		
ignitability (cigarette test)		BS 5852 part 1 (1979) from The Furniture and Furnishing (Fire) (Safety) regulations: 1988 No. 1324. Schedule 4 part 1 Ignition source 0: cigarette	СТІ		passed						

Processing specifications

Minimum workable width in centimeters	± 143					
Roll length in meters	± 40					
Material weight in grams per linear meter	± 590					
Test	Test specification	Executed by	Unit	Testresult	Norm RAL GZ 430/4:2019-01	Norm DIN EN

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Tensile strength	DIN EN ISO 13934-1:2013-08	CTL	Newton	1.878	1.028	min. 350	min. 400	A/A
Tear growth resistance	DIN EN ISO 13937-3:2000-06	CTL	Newton	159,0	74,1	min. 25	min. 30	A/A
Resistance to seam slippage	DIN EN ISO 13936-2:2004-07. Load 180 N	CTL	mm	1,7	1,3	max. 5	max. 4	A/A
Delamination	DIN 53530:1981-02	CTL	Newton	49,0	43,7	n/a	n/a	n/a
Chemical substances	REACH	Centexbel		passed				
	Oeko-Tex, product class II	Centexbel		certified				

Cleaning specifications

Cicuming Specifications									
Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09	
				Warp	Weft	DGM	DGM+		
Dimensional change for washing 30 degrees celcius / air drying	DIN EN ISO 5077:2008-04, DIN EN ISO 6330:2013-02, DIN EN ISO 3759:2011-08	CTL	%	-0,4	-1,2	n/a	n/a	A/A	











- We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.











